

# Altera Spa

# The Best for Less.

# ALTERA SPA



You'll be hard pressed to find a more dependable, more practical pedicure spa than our Altera Spa. This affordable spa incorporates the fine sense of style, sophistication and performance for which European Touch is known, and offers the ideal solution for salons just starting out or expanding their capabilities by adding spa pedicure services for the first time. For these reasons, it's no wonder the Altera Spa has become one of the most popular in the industry for economy, reliability and efficiency. Your clients will love our seat-back roller massage with vibration. For those demanding the best for less, the Altera Spa can't be beat.

Now available with Clean Touch Pipe-Free Technology! Our latest development, Clean Touch Pipe-Free technology is now available in the Altera Spa. Give your clients and salon top-notch sanitation control with the option of Clean Touch Pipe-Free Technology or our traditionally piped whirlpool movement.


### Base Colors



### Trim Colors



### Cushion Colors



Optional side trays act as a table for client conveniences and manicure services.

Remote unit allows fingertip control of the seat's massage settings.

The comfortable footrest can be adjusted in three positions, while the convenient hand sprayer makes rinsing out the basin easy.

The Altera Spa comes standard with traditional piped whirlpool style foot bath, featuring a quality pump motor and two multi-directional jets. Upgrade to our Clean Touch Pipe-Free technology!

The standard roller massage cushion encompasses built-in massage rollers and vibration motor for the ultimate in client comfort.



# ALTERA SPA

## Dependable and efficient.

Standard roller massage cushion provides both roller and vibration massage settings for client comfort and versatility.

Both armrests open to provide easy access to the chair.

Faucet and water controls are conveniently located for optimum technician efficiency.

The comfortable footrest adjusts in three positions.

The convenient hand sprayer makes rinsing the basin quick and easy.



We have a solution that's right for your salon or spa. Call for more information and a free consultation.




**EUROPEAN TOUCH™**  
800.626.6912  
www.europeantouch.com

## PEDICURE SPA SPECIFICATIONS

Hot and cold water supply lines required (hot and cold shut off valves may be installed under pedicure spa base)

Drain installation: References noted on pages nine through eleven, can be installed with optional power drain pump or as gravity drain.

Overall dimensions without accessories, seat upright: 54" (138cm) L x 32" (79cm) W x 56" (143cm) H\*

Without accessories, seat collapsed: (shipping position): 54" (138cm) L x 32" (82cm) W x 36" (92cm) H\*

Shipping dimensions: 55" (140cm) L x 33" (84cm) W x 41" (105cm) H\*

Empty weight: 150 lbs (68kg)\*

Shipping weight: 205 lbs (93kg)\*

Capacity of basin: 5.75 U.S. Gallons (21.8L) = Clean Touch™ Pipe-Free®\*

Whirlpool pump motor: 110V: 1/6 HP, 110V, 60HZ (alternate voltages available) (3/4 HP for Traditional Whirlpool - with Jets)

220V: 1/6 HP, 110V, 50Hz (alternate voltages available) (3/4 HP for Traditional Whirlpool - with Jets)

Alter seat and back movement: 2 infinitely adjustable lockable gas cylinders for reclining/sliding. The Altera requires 12" (31cm) of space between pedicure spa and wall in order for seat to recline to its fullest extent.\*

Massage motor: 12V AC, Adapter included (alternate voltages available)

Power source: 110V: 110V AC / 15 Amp, 60 Hz (GFCI Protected)

220V: 220-240VAC, 50Hz, 7.5 Amp (GFCI Protected)

Caution: Pedicure spa must be installed by a licensed electrician and a licensed plumber, conforming to all local and national electrical codes.

Construction: Linear Low Density Polyethylene (LLDPE), self-contained, pre-plumbed Clean Touch™ Pipe-Free® Technology with four water massage channels. No closed loop circulating pipes, fully drained.

Electrical switches: On/Off switch for whirlpool pump. Hand-held low voltage remote controls for massage motors, heat, and seat/back position. Hot and Cold water supply lines required.

UL listed/CE certified: Complies with ASME/ANSI Whirlpool Basin Specs ASME/ANSI A112.19 7M-1995 and A112.19.8M-1995. Backflow Protection Devices for Faucets with Side Spray: Check valves comply with ANSI/ASME A112.18.3M, A112.18.1M, and CSA B125.

Performance Limits:

1. This unit may lose one or more functions when electrostatic contact discharge in excess of 4KV gets into accessible conductive part of the unit and could be restored by resetting the unit.
2. This unit may lose one or more functions when power surge in excess of 2KV is applied to the AC input power port and could be restored by resetting the unit.
3. This unit may lose one or more functions when subjected to fast transient voltages in excess of 0.5KV at 5 KHz repetition frequency and could be restored.

Limited warranty: One (1) year from date of purchase.

\*Note: All dimensions and weights are approximate

---

NOTE: Due to our policy of continuous improvements, all specifications are subject to change without notice. All dimensions and weights are approximate.