

# Calais Spa

Designer. Custom. Chic.



This finely crafted custom pedicure unit creates the perfect combination of performance and sophistication. Other styles and configurations available, all with your choice of finishes and cushion color. Whether it is seating for two or ten, let us create something beautiful just for you. Clean Touch Pipe-Free Technology provides exceptional sanitation control while maintaining the invigorating water massage benefits for which European Touch is known. All components that come in contact with water may be easily removed, cleaned and sanitized, providing each client the purest beginning to any pedicure service. Each basin includes a handheld spray faucet, pivoting leg rests, and utilizes a minimal 4.5 gallons of water per pedicure service. Clean Touch Pipe-Free Technology is also available on other European Touch pedicure spas.

## CALAIS SPA

Exceptional sanitation control.

### Base Colors




Calais Pedicure Basin including Clean Touch sink with oversized chair with 3 zone massage and heat, that rotates 360 degrees and manual 2" front-to-back adjustment.



Model #50016000

### Cushion Colors



Calais Pedicure Basin including Clean Touch sink with Solaire chair that rotates 360 degrees and 2" front-to-back adjustment.



Model #50016001

Single Calais Pedicure Basin shown in Ivory and Cocoa Maple.



Model #50016201

Clean Touch Drop-In Basin comes with easily accessed water controls, handy pull-out sprayer, and with an optional power drain pump for quicker draining after your pedicure service.

Adjustable leg supports keep your clients comfortable while your technicians provide pedicure services.

Using only 4.5 gallons of water per pedicure, our Clean Touch Drop-In basin is the smart answer for salons where water usage is a concern, or any salon looking to "go green".

Simplicity reigns supreme with Clean Touch Pipe-Free technology. Incorporating a spinning impeller inside a compact, removable cover to create an under-and-around-the-foot water massage.



We have a solution that's right for your salon or spa. Call for more information and a free consultation.



  
EUROPEAN TOUCH™

800.626.6912  
www.europeantouch.com

## PEDICURE SPA BASIN SPECIFICATIONS

### PEDICURE SPA BASIN SPECIFICATIONS

Hot and cold water supply lines required (hot and cold shut offs may be installed under pedicure spa base)

#### SHIPPING INFORMATION

Dimensions: 48"L (122cm) x 40W (102cm) x 32"H (82cm) – includes Spa, carton, and pallet  
Weight: 130 lbs. (286 kg) - includes spa, carton, pallet

#### SPA INFORMATION

Overall dimensions: 27.25"L (70cm) x 23.25"W (59cm) x 18.25"H (47cm)  
Empty weight: 40 LBS  
Water Fill Line Capacity: 4.5 U.S. gallons  
Motor: 115V: 1/6 HP, 110V, 60Hz  
Power source: 115V: 115V AC, 2.75 Amps, 60 Hz (GFCI Protected) OR  
230V: 230V AC, 2.75 Amps, 50/60 Hz (GFCI Protected)  
Caution: Pedicure spa must be installed by a licensed electrician and a licensed plumber, conforming to all local and national electrical codes  
Construction: Acrylic basin, pre-plumbed  
Chair Specifications: Recommended vertical dimension from seat bottom to basin bottom 14 – 16"  
Clean Touch™ Pipe-Free® Technology: 4 water massage channels, no closed loop circulating pipes, fully drained, easy to clean and sanitize.  
Electrical switches: On/Off membrane switch for motor control and optional power drain pump.  
Compliances: Designed to comply with CAN/CSA-E60335-1:1994, CAN/CSA-E60335-2-32:2001, UL 60335-1:2002, & UL 1647:2001  
Electrostatic Limits: This unit may lose one or more functions when electrostatic contact discharge in excess of 4KV gets into accessible conductive part of the unit and could be restored by resetting the unit.  
This unit may lose one or more functions when power surge in excess of 2KV is applied to the AC input power port and could be restored by resetting the unit.  
This unit may lose one or more functions when subjected to fast transient voltages in excess of 0.5KV at 5 KHz repetition frequency and could be restored.  
Limited warranty: One (1) year on parts from date of shipment. Labor is not included.

---

NOTE: Due to our policy of continuous improvements, all specifications are subject to change without notice.  
All dimensions and weights are approximate